



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

REC'D 20 AUG 2004

WIPO

PCT

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

**Patentanmeldung Nr. Patent application No. Demande de brevet n°**

03291705.6

BEST AVAILABLE COPY

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Anmeldung Nr:  
Application no.: 03291705.6  
Demande no:

Anmeldetag:  
Date of filing: 09.07.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Deutsche Thomson-Brandt GmbH  
Hermann Schweer Strasse 3  
78048 Villingen-Schwenningen  
ALLEMAGNE  
Thomson Licensing S.A.  
46, quai Alphonse Le Gallo  
92648 Boulogne Cedex  
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se referer à la description.)

Error correction method for reed-solomon product code

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

H03M13/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

# Error correction method for Reed-Solomon product code

The present invention relates to soft-decision decoding of Reed-Solomon product codes. It further relates to a system for correcting errors in a Reed-Solomon product code.

For optical recording media such as digital versatile disks (DVD) a Reed-Solomon (RS) product code is used for error correction. The data frames include horizontal and vertical parity data for correcting errors in the frame per rows and columns. The data rows and columns of the frame constitute so-called product-codes. The outer code is a RS code(208,192,17), while the inner code is a RS code(182,172,11). Therefore, one data frame consists of  $208 \times 182 = 37856$  bytes.

Multipass devices save at least two data frames in a memory. One data frame is saved for input/output and the second is saved for correction. Current systems save the data either in external SDRAM or in internal SRAM. Due to random accesses during correction of the errors, the SDRAM approach is significantly slower than the approach using internal SRAM.

US 6,032,283 discloses an implementation of a DVD controller. The input/output streaming and correction is done in an external SDRAM. For fast processing an internal SRAM is used. The syndromes are saved in the internal SRAM, while correction is done in the external SDRAM. During correction the orthogonal syndromes are updated with the error values. Therefore, additional hardware is required, but the process is accelerated. The disclosed implementation has a disadvantage that random accesses to the SDRAM are required, which slow down the correction. The internal SRAM consumption for multipass correction in that implementation is about  $2 \times 4992 = 9984$  bytes.

It is an object of the invention to propose an improved method for error correction.

According to the invention, this object is achieved by a method for error correction of an encoded data stream comprising the steps of:

- 5 - saving the demodulated data stream in a small input buffer;
- performing a first correction process on-the-fly in the input buffer;
- transferring the data to an external SDRAM after correction;
- copying a data frame from the external SDRAM to an embedded
- 10 SRAM;
- starting a multipass correction in the embedded SRAM; and
- copying the corrected data frame back from the embedded SRAM to the external SDRAM.

The method uses a mixture of external SDRAM and internal SRAM.

- 15 The input/output streaming is performed by a comparatively slow external SDRAM, while the correction is performed in a fast internal SRAM. Therefore, the data from the external SDRAM are copied into the fast internal SRAM only for correction. After the correction process, the so-called "Inner 1", the data is
- 20 streamed back to the external SDRAM. In this way the number of random accesses to the external SDRAM is reduced. If the errors are sorted, the "Inner 1" correction process and the transfer of the data can be performed at same time. Furthermore, the size of the internal SRAM is also reduced. The internal SRAM
- 25 correction simplifies the hardware complexity during the correction process.

- 30 Favourably, the data stream is encoded with a Reed-Solomon product code. This type of error correction code is widely used for coding data streams on recording media.

- 35 A method according to the invention is advantageously performed by a device for error correction of an encoded data stream. Such a device has the advantage that the required SRAM and the random accesses to the SDRAM are reduced. Furthermore, due to

the internal SRAM approach high multipass correction is enabled.

5 Favourably, a method or a device according to the invention is used by an apparatus for reading from and/or writing to recording media.

For a better understanding of the invention, an exemplary embodiment is specified in the following description with  
10 reference to the figures. It is understood that the invention is not limited to this exemplary embodiment and that specified features can also expediently be combined and/or modified without departing from the scope of the present invention. In the figures:

15 Fig. 1 shows a block diagram of acquisition and the horizontal pass 1;

Fig. 2 shows the process flow of the multipass correction;  
20 and

Fig. 3 shows a data flow timing of SRAM2/SDRAM.

In the following the invention is described with reference to  
25 optical systems used for digital versatile disks. Of course, the invention is also applicable to other types of disk systems.

On a DVD the input data are packed in ECC blocks. An error  
30 correction code (ECC) block comprises 208 rows times 182 columns of symbols, whereby one symbol corresponds to one byte.

For decoding a DVD data frame the following procedures are performed:

- 35
- Input and sort the data according to the frame numbers
  - Deinterleave the ECC block

- Correct ECC horizontal (PI-correction; inner correction)
- Correct ECC vertical (PO-correction; outer correction)
- Multipass: Perform horizontal and vertical correction again, if necessary
- 5 • Descramble data frame
- Perform EDC (error detection code) check on data frame

Two types of corrections are processed in the data flow:

- Horizontal: correcting 208 rows with (182,172,11) RS codes
- 10 • Vertical: correcting 182 columns with (208,192,17) RS codes

According to the invention an input buffer 2 and one SRAM bank 11 holding the data for one ECC block is used. The first  
15 correction pass, the so-called "inner1" correction, is done on-the-fly, while the multipass correction is done in the embedded SRAM bank 11. A brief description of the data-flow of the two correction processes is given in the following.

- For the first correction process, the demodulated data stream  
20 of a set  $ECC_n$  is saved in a small embedded SRAM 2, referred as "input buffer". The correction of the set  $ECC_n$  is performed on-the-fly in the embedded SRAM 2. After correction of inner1 the data of the set  $ECC_n$  are transferred to an external SDRAM 3.
- For the second correction process, after receiving a full set  
25 of  $ECC_n$  in the external SDRAM 3 the multipass corrected data of a previous set  $ECC_{n-1}$  is read out from the embedded SRAM 2 11 back to the external SDRAM 3 while the block  $ECC_n$  is copied from the SDRAM 3 to the SRAM 2 11. After receiving a full set of  $ECC_n$  in the embedded SRAM 2 11, the multipass correction is started.
- 30 Both processes work independently from each other.

- In Fig. 1 a block diagram of acquisition and the horizontal pass 1 is shown. An input controller 1 saves one row of  $ECC_n$  in the input buffer 2. The input controller 1 detects streaming  
35 discontinuities. Any discontinuities of less than one row

(byte/frame) are corrected immediately in the input buffer 2. If streaming discontinuities of more than one row are detected, this information is stored and the row is written to the correct position of the SDRAM 3 by a deinterleaver 4. After  
5 completing one row, the input controller 1 starts a horizontal syndromes unit 5. The horizontal syndromes unit 5 reads the row from the input buffer 2 and computes modified syndromes and an erasure polynomial. A key solver and Chien unit 6 solves the equation and transfers the error values and positions to a  
10 correction unit 7. The positions of the first ten acquisition errors are stored in a first erasure memory 8. The correction unit 7 corrects the data of block  $ECC_n$  in the input buffer 2 in a bitwise access row by row. If a row is uncorrectable, the row number is marked as uncorrectable. Therefore, a status bit  
15 is attached to the row, indicating if the obtained codeword is correct or not. After correction one row, the row is transferred to the external SDRAM 3 via the deinterleaver 4, taking into account the row number information from the input controller 1. If necessary, the deinterleaver 4 jumps row-wise  
20 in the SDRAM 3 to correct streaming discontinuities detected by the input controller 1. After acquisition of one complete  $ECC_n$ , the second process of multipass correction is initiated.

After receiving one full set of  $ECC_n$  in the SDRAM 3, the data  
25 are copied to the SRAM2 11. While new ECC is streamed through the SRAM1 2, the vertical and subsequently the multipass correction is performed in the embedded SRAM2 11. The process flow of the multipass correction is shown in Fig. 2. In the figure, in case a pair of numbers is given, the numbers in  
30 brackets refer to horizontal correction, while the numbers without brackets refer to vertical correction. A copy unit 9 copies the data of the ECC into the embedded SRAM2 11. It further writes the status bit into the status memory 12 of the "Inner1" pass and computes the erasure positions of  
35 uncorrectable errors, which are written into a second erasure memory 10. The second erasure memory 10 stores the positions of ---

up to 16 rows/10 columns, which were uncorrectable in the previous correction process. After receiving a full ECC, a control unit 14 is started. The control unit 14 reads the last written status of the codeword from the status memory 12.

- 5 According to this status the process for the codeword is started. The syndrome generator 5 reads the erasure of the last orthogonal process and computes the syndromes of the codeword. After computation of the syndromes, it starts the key solver and Chien 6 search algorithm with the syndromes and the last
- 10 orthogonal erasure positions. The correction unit 7 corrects the ECC block in the SRAM2 11 in a bitwise access, saving the status of the codeword back into the status memory 12. An output/descrambler 13 descrambles the data stream, performs an EDC check, and copies the data back to a DRAM track buffer
- 15 area. The output/descrambler 13 may further perform a sector filtering.

The memory needed for the process flow can be summarized as follows:

- 20
- Erasure Memory1, 10 bytes per row of SRAM1
  - Status Memory, 390 bit = 49 bytes
  - Erasure Memory2, 16 bytes
  - SRAM1 < 4kbyte
  - SRAM2 37856 bytes
- 25

Figure 3 shows a more detailed timing structure of the SRAM behaviour. The streams between SRAM and SDRAM reduces the time left for multipass correction. From the figure it can be seen that the two processes described in Fig. 1 and Fig. 2 are

30 decoupled. The stream from the input buffer 2 to the SDRAM 3 is critically temporally linked to the data input, whereas the streams from the SDRAM 3 to the SRAM2 11 and from the SRAM2 11 to the SDRAM 3 can be transmitted discretionarily whenever the bus to the SDRAM 3 is empty. This only depends on the speed of

35 the SDRAM buffer.



## Claims

1. Method for error correction of an encoded data stream comprising the steps of:
  - 5 - saving the demodulated data stream in a small input buffer 2;
  - performing a first correction process on-the-fly in the input buffer 2;
  - transferring the data to an external SDRAM 3 after correction;
  - 10 - copying a data frame from the external SDRAM 3 to an embedded SRAM 11;
  - starting a multipass correction in the embedded SRAM 11; and
  - copying the corrected data frame back from the embedded SRAM 11 to the external SDRAM 3.
- 15 2. Method according to claim 1, characterized in that the data stream is encoded with a Reed-Solomon product code.
3. Device for error correction of an encoded data stream,  
20 characterized in that it performs a method according to one of claims 1 or 2.
4. Apparatus for reading from and/or writing to recording media, characterized in that it uses a method according to  
25 anyone of claims 1 to 2 or comprises a device according to claim 3 for error correction of an encoded data stream.

**Abstract**

Error correction method for Reed-Solomon product code

5 The present invention relates to soft-decision decoding of Reed-Solomon product codes.

According to the invention, a method for error correction of an encoded data stream comprises the steps of:

- saving the demodulated data stream in a small input buffer 2;
- 10 - performing a first correction process on-the-fly in the input buffer 2;
- transferring the data to an external SDRAM 3 after correction;
- copying a data frame from the external SDRAM 3 to an embedded
- 15 SRAM 11;
- starting a multipass correction in the embedded SRAM 11; and
- copying the corrected data frame back from the embedded SRAM 11 to the external SDRAM 3.

20 (Fig. 2)




Fig. 1




Fig. 2

3/3




Fig. 3

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**